



GREY LYNN, AUCKLAND
JASON BAILEY ARCHITECTS

DIAMOND OIL ACTIVE



Diamond Oil Active is a penetrating timber-finishing product that leaves a natural representation of wood. With Hyper Cross-Linking technology, the oil molecules form billions of extra bonds, which ensures a durable, hard-wearing surface that is highly water and dirt-resistant from just one coat. Diamond Oil Active is derived from vegetable oil components and has no VOC, so it is eco-friendly and non-harmful for an everyday living environment.

CARBON BLACK & BRAZIL BROWN
OAK VENEER CABINETRY & BENCH





CONCRETE GREY

AMERICAN OAK FLOORING & STAIRS





- 100% penetrating oil, not film-forming
- Vegetable oil based – truly sustainable
- 99% solid content
- No VOC (Volatile Organic Compound)
- Isocyanate-free
- Ingredients certified by the German Biological Building Institute (IBR)
- One coat, fast-drying product
- Available in 9 colours
- Suitable for all interior timber surfaces

APPLICATION PROCESS

DIAMOND OIL ACTIVE



1. Apply WOCA Wood Cleaner, diluted 1:40 with water, to the clean, dry surface.
2. Apply Diamond Oil Active to the surface sparingly using a speed brush or roller. Allow the product to penetrate.
3. After 20 minutes, rub the oil into the wood with a cloth, nylon pad, or 360° gib tool.
4. Remove all excess from the surface with a clean cloth.
5. Dispose of cloths in a plastic bag containing water to avoid self-combustion.

The wood will be dry after 48 hours, and fully hard after 7 days.

Clean and maintain with WOCA Natural Soap, diluted 1:40.



PREPARE • TREAT • MAINTAIN

Design Denmark
351 New North Road,
Kingsland, Auckland 1021
wocadenmark.com



wocanewzealand



wocanewzealand